

# Cordless IQ<sup>V</sup>™ Tools and Accessories | Impact Tools and Ratchets

## W3111

1/4"  Quick Change Hex - IQV20



- 384 Nm of Forward Torque
- 474 Nm of breakaway Torque
- 360° Shadowless Light
- 3 Output Modes
- Compact & Light Weight design
- Brushless Motor & Variable speed Trigger



Available in kits

Part Number

**W3111-K22-AP1**

**W3111-K22-JP**

**W3111-K22-KR**

1/4" QC Hex Impact Driver, Charger 12/20 V,  
2 BL2012 (2.5 Ah) Li-Ion Batteries

## W3131

3/8"  Square Anvil – IQV20



- 406 Nm of Forward Torque
- 542 Nm of breakaway Torque
- 360° Shadowless Light
- 3 Output Modes
- Compact & Light Weight design
- Brushless Motor & Variable speed Trigger



Available in kits

Part Number

**W3131-K22-AP1**

**W3131-K22-JP**

**W3131-K22-KR**

3/8" Impact Wrench, Charger 12/20 V,  
2 BL2022 (5.0 Ah) Li-Ion Batteries

## W3151

1/2"  Square Anvil – IQV20



- 433 Nm of Forward Torque
- 610 Nm of breakaway Torque
- 360° Shadowless Light
- 3 Output Modes
- Compact & Light Weight design
- Brushless Motor & Variable speed Trigger



Available in kits

Part Number

**W3151-K22-AP1**

**W3151-K22-JP**

**W3151-K22-KR**

1/2" Impact Wrench, Charger 12/20 V,  
2 BL2022 (5.0 Ah) Li-Ion Batteries

| Part Number | Battery | V     | in                                                                                       | Tighten/Breakaway<br>MAX<br>Nm | 1 min<br>rpm | 1 min<br>bpm | kg  | mm  | dB(A) | m/s <sup>2</sup> /K |
|-------------|---------|-------|------------------------------------------------------------------------------------------|--------------------------------|--------------|--------------|-----|-----|-------|---------------------|
| W3111       | BL2012  | IQV20 | 1/4"  | 384/474                        | 2,800        | 4,200        | 1.0 | 132 | 90    | 18.1/5.8            |
| W3131       | BL2022  | IQV20 | 1/2"  | 406/542                        | 2,800        | 4,200        | 1.0 | 132 | 90    | 18.1/5.8            |
| W3151       | BL2022  | IQV20 | 3/8"  | 433/610                        | 2,800        | 4,200        | 1.0 | 135 | 90    | 18.1/5.8            |