

Air Impacttools™ | 1/4" and 3/8"

2115Qi

3/8" ■ Ring type



- 407 Nm of maximum torque in reverse
- Only 1.13 kg and 151 mm
- Twin-hammer impact mechanism
- Aluminum hammer case and composite housing
- 4-position power regulator
- 1-hand forward and reverse switch

Also available

2125Qi

1/2" Ring type

Protection Boot

2115-BOOT

CCN: 45505351

211

3/8" ■ Ring type



- 204 Nm of maximum torque in reverse
- Only 1.09 kg
- Jumbo-hammer impact mechanism
- 5-position power regulator

212A

3/8" ■ Ring type



- 244 Nm of maximum torque in reverse
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability
- Wide range of power regulator settings helps adjusting the power to the application
- Only 1.31 kg

Also available

222A

1/2" Ring type

Protection Boot

212-BOOT

CCN: 45505344

Part Number	CCN	in	Nm	Nm	rpm	bpm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
2115Qi	45588076	3/8" □	407	34 - 312	15,000	1,500	1.13	151	1/4"	10	1.9	8.00	94.0	7.5/1.8
2125Qi	45604287	1/2" □	450	34 - 340	15,000	1,500	1.14	155.0	1/4"	10	1.9	8.00	94.00	7.5/1.8
211	1197060	3/8" □	204	27 - 170	10,000	1,500	1.09	168	1/4"	10	1.2	5.20	104.0	5.9/1.6
212A (222A-1/2" □)	45765294	3/8" □	244	27 - 170	10,000	1,500	1.31	152	1/4"	10	1.2	5.20	97.5	6.5/1.0

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)