

Air Impacttools™ | 1/2"

131S-EA

1/2" ■ Ring type



- 610 Nm, reverse bias
- Handle exhaust
- Twin-hammer impact mechanism
- 5-position power regulator

E131

1/2" ■ Ring type



- 678 Nm, reverse bias
- Front exhaust
- Twin-hammer impact mechanism
- Efficient performance at economical price

E132

1/2" ■ Ring type



- 750 Nm of maximum reverse torque
- Handle exhaust
- Twin-hammer impact mechanism
- 3-position Forward power regulator
- Efficient performance at economical price

MAX 1 min 1 min L MAX														
Part Number	CCN	in	Nm	Nm	rpm	bpm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
131S-EA	01372416	1/2"□	610	34 - 475	8,000	1,225	2.63	185	1/4"	10	2.0	-	90.7	5.2
E131	46811063	1/2"□	678	34 - 475	8,750	1,175	2.60	192	1/4"	10	2.0	13.60	98.0	7.8/2.4
E132	E132	1/2"□	750	40 - 600	10,000	1,250	2.40	187.3	1/4"	10	19.8	11.30	90.2	8.2/1.5

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)