

Air Ratchets

1077XPA

1/2" ■



- 73 Nm and 160 rpm
- Variable speed lever
- 360° adjustable exhaust

Also available

107XPA

3/8"

Protection Boot

107-BOOT

CCN: 80171853

1099XPA

1/2" ■



- 103 Nm and 220 rpm
- Variable speed lever
- 360° adjustable exhaust

Also available

109XPA

3/8"

Protection Boot

109-BOOT

CCN: 80181001

1770

1/2" ■



- 81 Nm of maximum torque
- Heat-treated head provides exceptional durability
- Variable speed lever allows precise delivery of power

Also available

170

3/8"

105-D3

3/8" ■



- 34 Nm and 250 rpm
- Only 0.64 kg and 186 mm
- Variable speed lever

Also available

105-D2

1/4"

105-C3

3/8" (Different gear holder & rotor to 105-D3)

105-L2

1/4"

Protection Boot

103-BOOT

CCN: 45649571

Part Number	CCN	in	Nm	Nm	rpm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
1077XPA	80171853	1/2" □	68	14 - 61	160	1.10	279	1/4"	10	1.42	8.50	94.4	<2.5
107XPA	80171705	3/8" □	68	14 - 61	160	1.10	279	1/4"	10	1.42	8.50	94.4	<2.5
1099XPA	80181001	1/2" □	103	14 - 87	220	1.40	302	1/4"	10	1.88	11.33	92.4	2.5/0.7
109XPA	16578700	3/8" □	95	14 - 87	220	1.40	302	1/4"	10	1.88	11.33	92.4	2.5/0.7
1770	80103799	1/2" □	81	81	160	1.17	262	1/4"	10	1.90	10.00	94.8	2.8/0.7
170	80103781	3/8" □	81	81	160	1.16	262	1/4"	10	1.90	10.00	94.8	2.8/0.7
105-D3	45649738	3/8" □	34	7 - 27	250	0.64	186	1/4"	10	1.42	8.50	81.8	5.1/0.9
105-D2	45649571	1/4" □	34	7 - 27	250	0.64	186	1/4"	10	1.42	8.50	81.8	5.1/0.9
105-C3	45662293	3/8" □	34	7 - 27	250	0.64	186	1/4"	10	1.42	8.50	81.8	3.5/1.2
105-L2	45650660	1/4" □	34	7 - 27	250	0.71	214	1/4"	10	1.42	8.50	81.8	3.7/0.9

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)