

Air Hammers



119MAX

Round shank



- Stroke: 89 mm
- 2,530 blows per minute
- Contains: quick-change retainer

Available in kits

119MAXK

Round shank

CCN: 119MAXK



Hammer + Quick-Change Retainer and 5 Chisels

123MAX

Round shank



- Stroke: 67 mm
- 3,530 blows per minute
- Contains: quick-change retainer

Available in kits

123MAXK

Round shank

CCN: 123MAXK



Hammer + Quick-Change Retainer and 5 Chisels

135MAX

Round shank



- Stroke: 76 mm
- 2,600 blows per minute
- Contains: quick-change retainer

Available in kits

135MAXK

Round shank

CCN: 135MAXK



Hammer + Quick-Change Retainer and 5 Chisels

Part Number	CCN	 1 min							 MAX		
		bpm	mm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
119MAX	119MAX	2,530	89	2.0	231.9	1/4"	10	-	11.2	95.7	4.5 /2.3
123MAX	123MAX	3,530	67	1.8	182.9	1/4"	10	-	11.4	95.0	5.9/4.2
135MAX	135MAX	2,600	76	2.0	220.1	1/4"	10	-	1.3	98.0	5.4/2.9

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)