

Air Hammers | Round shank | Needle Scaler

121-EU

Round shank



- Stroke: 58 mm
- 3,000 blows per minute

Also available

121/Q-EU

Hexagonal shank

115

Round shank



- stroke: 41mm
- 5000 blows per minute

116

Round shank



- Stroke: 67 mm
- 3,500 blows per minute
- Power regulator

Also available

116H

Hexagonal shank

117

Round shank



- Up to 2,000 blows per minute
- Alloyed steel barrel and heat-treated piston for longer life
- Built-in power regulator and trigger control

132

Round shank



- Up to 1,725 blows per minute
- Alloyed steel barrel and heat-treated piston for longer life
- Built-in power regulator and trigger control

125

Needle scaler



- Stroke: 28 mm
- 4,600 blows per minute
- Contains: steel needles

Part Number	CCN	bpm	mm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
121-EU	04352746	3,000	58	1.59	194	1/4"	10	1.40	7.10	95.3	19.9/4.6
121/Q-EU	01343698	3,000	58	1.59	194	1/4"	10	1.40	7.10	95.3	19.9/4.6
115	01216175	5,000	41	1.18	155	1/4"	10	0.95	6.60	101.3	14.8/2.2
116	01216183	3,500	67	1.54	198	1/4"	10	1.40	7.10	104.4	14.8/2.2
116H	01233501	3,500	67	1.54	198	1/4"	10	1.40	7.10	104.4	14.8/2.2
117	01216191	2,000	89	1.86	251	1/4"	10	1.40	6.60	103.5	9.2/3.0
132	01173525	1,725	102	1.54	216	1/4"	10	1.40	5.20	-	-
125	01348200IRI	46,000	-	2.83	465	1/4"	8	3.80	7.10	96.6	8.3/1.3

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)