

Air Drills, Screwdrivers and specialty tools | Drills

7803A

Standard chuck



- 13 mm (1/2 in) chuck
- 0.37 kW (0.50 HP)
- 500 rpm

Also available

7803AKC

Keyless chuck

7803RA

Standard chuck, reversible

7803RAKC

Keyless chuck, reversible

Protection Boot

7803-BOOT

CCN: 80113632

7802A

Standard chuck



- 10 mm (3/8 in) chuck
- 0.37 kW (0.50 HP)
- 2,000 rpm

Also available

7802AKC

Keyless chuck

7802RA

Standard chuck, reversible

7802RAKC

Keyless chuck, reversible

Protection Boot

7802-BOOT

CCN: 80113616

7807R-A

Standard chuck, reversible



- 10 mm (3/8 in) standard chuck
- 0.25 kW (0.33 HP)
- 1,800 rpm
- Reversible

LA410-EU

Standard chuck



- 10 mm (3/8 in) standard chuck
- 0.25 kW (0.33 HP)
- 4,500 rpm

Part Number	CCN	SIZE	kWatt	1 min		L			MAX			
		mm	kW	rpm	kg	mm	NPT	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
7803A	80113632	13	0.37	500	1.64	195	1/4"	10	1.9	12.70	83.0	<2.5
7803AKC	10563724	13	0.37	500	1.63	200	1/4"	10	1.9	12.70	83.0	<2.5
7803RA	80113673	13	0.37	500	1.64	195	1/4"	10	1.9	12.70	83.0	<2.5
7803RAKC	10563732	13	0.37	500	1.63	200	1/4"	10	1.9	12.70	83.0	<2.5
7802A	80113616	10	0.37	2,000	1.31	163	1/4"	10	1.9	12.70	83.0	2.8/0.7
7802AKC	10563716	10	0.37	2,000	1.35	175	1/4"	10	1.9	12.70	83.0	2.8/0.7
7802RA	80113640	10	0.37	2,000	1.30	163	1/4"	10	1.9	12.70	83.0	2.8/0.7
7802RAKC	80147424	10	0.37	2,000	1.35	175	1/4"	10	1.9	12.70	83.0	2.8/0.7
7807R-A	7807R-A	10	0.25	1,800	1.13	205	1/4"	10	1.5	9.70	87.0	2.49
LA410-EU	01328616	10	0.25	4,500	0.91	228	1/4"	10	1.4	12.80	84.9	2.9/0.7

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Performance at 6.2 bar (90 psi)